

B¹ c1
cont

a locking sleeve in detachable, re-attachable engagement with said insertion end of said connector body for securing said cable in said connector body, wherein said locking sleeve is movable from a first position loosely retaining said cable in said connector body to a second position locking said cable to said connector body.

B² c2

3. (Amended) A coaxial cable connector of claim 1 wherein said movement from said first position to said second position is along a linear direction.

B³ c3

5. (Amended) A connector for terminating a coaxial cable having a center conductor, an insulator surrounding said center conductor, a shield surrounding said insulator and a jacket covering said shield, said connector comprising:

a connector body for receiving said cable, said body having a receiving end for insertably receiving said cable and an opposed connection end for extension of said center conductor therefrom; and

a locking sleeve in resilient detachable, re-attachable engagement with said insertion end of said connector body for securing said cable in said connector body, wherein said locking sleeve is movable between a first position wherein said cable is loosely retained in said connector body to said second position locking said cable to said connector body.

B⁴

7. (Amended) A connector of claim 6 wherein said locking sleeve is axially movable from said first position to said second position.

Please add the following new claims:

Sub 4
B5

--20. A coaxial cable connector comprising:
a connector body having a cable receiving end on opposed connector end; and
a locking sleeve in detachable, re-attachable engagement with said receiving end of said
connector body for securing said cable in said connector body, wherein said locking sleeve is
movable from a first detachable position loosely retaining said cable in said connector body to a
second inseparable position locking said cable to said body.--

--21. A coaxial cable connector of claim 20 wherein said locking sleeve is positionable in
surrounding engagement with said cable.--

--22. A coaxial cable connector of claim 20 wherein said locking sleeve is movable from said
first position to said second position along a linear direction.--